


NO.	SYMBOL
1	NC
2	NC
3	NC
4	NC
5	LEDA
6	LEDK
7	VSS
8	VDD
9	V0
10	RS
11	Rw
12	E
13	D0
14	D1
15	D2
16	D3
17	D4
18	D5
19	D6
20	D7

CN: FC-20P
WIRE: AWG#28



- NOTE:
1. GENERAL TOLERANCE: ±0.20.
2. (<...>) IS REFERENCE DIMENSION.
3. * CRITICAL DIMENSION
4. RoHS COMPLIANT

Display Type	DFSTN
	NEGATIVE
	TRANSMISSIVE
Front Polarizer	
Operating Method	1/16 DUTY/3 BIAS
Viewing Angle	6 O'CLOCK
LED Driver IC	MT6303-80T01
Operating Voltage	VGF=5.0V VDD=5.0V
Operation Temperature	-20°C TO 70°C
Storage Temperature	-30°C TO 80°C
High Temperature/Humidity Storage	
Connector Type	CONNECTOR
Backlight	WHITE If=15mA Vf=3.2±0.3V

VER.	SYMBOL	AMENDMENT	SIGN	DATE	CUSTOMER'S APPROVAL	TITLE	DRAWING NO.	UNIT	mm	SCALE	FIT
01		first issue	ZDL	12.08.16		MODULE SPEC.	STR-TC9128				
						BOM NO.:120814-02A		3rd Angle			SHEET 1 OF 1
						TRUEVISION TECHNOLOGIES LTD					