



NO.	SIGNAL
1	CSB
2	RSTB
3	A0
4	/RW
5	/RD
6	D0
7	D1
8	D2
9	D3
10	D4
11	D5
12	D6
13	D7
14	VDD
15	VSS
16	V0
17	XV0
18	VG
19	C86
20	PSB

Display Type	FSTN
	POSITIVE
	REFLECTIVE
Front Polarizer	NORMAL
Driving Method	1/65 DUTY,1/9 BIAS
Viewing Direction	6 O'CLOCK
LCD Driver IC	ST7567
Logic Voltage (V)	3.0V
LCD Driving Voltage	9.0V
Operation Temperature	-20°C TO 60°C
Storage Temperature	-30°C TO 70°C
Interface	6800/8080
Backlight	✓

- NOTES:
1. GENERAL TOLERANCE±0.2.
 2. (...) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. RoHS COMPLIANT.



					ME.CHECKED	LJW	TITLE MODULE SPEC.	DRAWING NO. STR-TG9201				
					EE.CHECKED	JLF		BOM NO. :BM130909-14A	UNIT	mm	SCALE	FIT
					PE.CHECKED	JLF			3rd Angle		SHEET 1 OF 1	
					APPROVED	HJB						
01	FIRST ISSUE		LJW	13. 10. 09	CUSTOMER'S APPROVAL		TRUEVISION TECHNOLOGIES LTD					
VER.	SYMBOL	DESCRIPTION OF CHANGES	SIGN	DATE								