



**PIN ASSIGNMENT:**


1	VB0+	16	WR0
2	VB1+	17	CD
3	VB1-	18	CS0
4	VB0-	19	RST
5	VA0+	20	D0
6	VA1+	21	D1
7	VA1-	22	D2
8	VA0-	23	D3
9	VLCD	24	D4
10	VDD	25	D5
11	VSS	26	D6
12	TST4	27	D7
13	BM0	28	NC
14	BM1	29	K
15	WR1	30	A



LCD LAYOUT



BACKLIGHT LED CIRCUIT(6PCS LED)



DOTS SIZE  
SCLAE:20/1

1. GENERAL TOLERANCE: ±0.3.
2. (...) IS REFERENCE DIMENSION.
3. \* CRITICAL DIMENSION
4. COMPLYABLY RoHS.

	FSTN
	POSITIVE
	TRANSFLECTIVE
FRONT POLARIZER	NORMAL
OPERATING METHOD	1/128DUTY
	1/11BIAS
OPERATION VOLTAGE	VDP=16V VDD=3V
VIEWING ANGLE	6:00
OPERATION TEMPERATURE	-20°C TO 70°C
STORAGE TEMPERATURE	-30°C TO 80°C
LCD DRIVER IC	UC1611S
CONNECTOR TYPE	PIN
	WHITE
BACKLIGHT COLOR	If=60-120mA,Vf=3.3V

01	First Issue	WKL	16.05.10	EE.CHECKED	HJB	TITLE MODULE SPEC.	DRAWING NO. STR-TG9204				
VER.	SYMBOL	AMENDMENT	WKL	ME.CHECKED	HJB		BOM NO.:BM130922-05A	UNIT	mm	SCALE	FIT
			WKL	APPROVED	HJB		3rd Angle		SHEET	1 OF	1
				CUSTOMER'S APPROVAL		TRUEVISION TECHNOLOGIES LTD.					