



PIN ASSIGNMENT

Pin No	Symbol
1	VLCD
2	VB0-
3	VB1-
4	VB1+
5	VB0+
6	VDD
7	VSS
8	PDR
9	NC
10	CS0
11	CD
12	RSTB
13	SCK<D0>
14	SDA
15	NC
16	IT0-VSS
17	A
18	K



Details "A"
scale 10:1



- NOTE:
 1. GENERAL TOLERANCE: ±0.30.
 2. (..) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. COMPLIABLY RoHS.

DISPLAY TYPE	FSTN POSITIVE TRANSMISSIVE
FRONT POLARIZER	
OPERATING METHOD	1/65DUTY,1/9BIAS
OPERATION VOLTAGE	VDP=9.0V,
VIEWING ANGLE	6:00
OPERATION TEMPERATURE	-20°C TO 70°C
STORAGE TEMPERATURE	-30°C TO 80°C
CONNECTOR TYPE	FPC
LCD CONTROLLER/DRIVER	UC1609c
BACKLIGHT COLOR	WHITEVF=50 IF=20mA(TYP)

VER.	SYMBOL	AMENDMENT	SIGN	DATE	CUSTOMER'S APPROVAL	DRAWN	ZQ	TITLE	DRAWING NO.			
01		First issue	ZQ	14.02.28				MODULE SPEC.	STR-TG9248			
									UNIT	mm	SCALE	FIT
									3rd Angle		SHEET 1 OF 1	
								BOM NO.: BM130407-03A	TRUEVISION TECHNOLOGIES LTD.			