




NO.	SIGNAL	NO.	SIGNAL
1	GND	16	GND
2	NC	17	GND
3	NC	18	SCL
4	NC	19	SDA
5	NC	20	VI028
6	LED+	21	GND
7	LED-	22	GND
8	GND	23	GND
9	VI018	24	GND
10	GND	25	GND
11	GND	26	NC
12	GND	27	V0(NC)
13	CS	28	NC
14	RST	29	GND
15	A0	30	GND

- NOTE:
1. GENERAL TOLERANCE: ±0.3.
 2. (...) IS REFERENCE DIMENSION.
 3. COMPLYABLY ROHS.
 4. * CRITICAL DIMENSION.



DISPLAY TYPE	FSTN
	POSITIVE
	TRANSMISSIVE
FRONT POLARIZER	
OPERATING METHOD	1/65 DUTY
OPERATION VOLTAGE(VDP)	1/7 BIAS
VIEWING ANGLE	VDP=6.5V VDD=2.8V
OPERATION TEMPERATURE	6:00
STORAGE TEMPERATURE	-10°C TO +60°C
INTERFACE	-20°C TO +70°C
CONNECTOR TYPE	SPI
LCD DRIVER IC	FPC
BACKLIGHT COLOR	IST3080
	White
	If=15mA, Vf=3.0±0.2V

VER.	SYMBOL	AMENDMENT	SIGN	DATE	DRAWN	ZX	TITLE	DRAWING NO.
					EE.CHECKED	JJQ	MODULE SPEC.	STR-TG9500A
					PE.CHECKED	HJB		UNIT mm SCALE FIT
					APPROVED	HJB	BOM NO.: BM150710-01A	3rd Angle SHEET 1 OF 1
O1		First issue	ZX	15.10.21	CUSTOMER'S APPROVAL		TRUEVISION TECHNOLOGIES LTD.	